



GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL PASSION 4T

API SN, SAE 20W-40

FOUR-STROKE MOTORCYCLE ENGINE OIL

DESCRIPTION

ADROL PASSION 4T 20W40 API SN is specially formulated oil for the engine, transmission and a wet clutch of new generation 4- Stroke two wheelers.

APPLICATIONS

- Air and liquid-cooled four-stroke motorcycle engines
- Particularly suitable for Japanese high performance motorcycle engines
- Motorcycles with and without oil immersed clutches
- Motorcycles with combined engine/transmission units or separate gear boxes where a multigrade engine oil is specified
- Motorcycles with back torque limiters
- Motorcycles with exhaust catalytic converters
- Latest generation, four-stroke scooter engines
- Four-stroke gasoline engines fitted to portable power equipment, such as generators, mowers, etc

PERFORMANCE STANDARDS

- API SN
- JASO MA2

BENEFITS

- Prolongs engine life
- Saves on maintenance
- Lively throttle response
- Good all-temperature protection

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: www.adrollubricants.com Email: info@adrollubricants.com Customer Care No.: 8285005500





GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

KEY PROPERTIES

SAE GRADES	20W-40
Appearance	Red
Viscosity @ 100°C (mm ² /s)	15 cSt
Viscosity @ 40°C (mm ² /s)	128.62 cSt
Viscosity Index	126
Pour Point (°C)	-18
Flash Point (°C)	220
TBN, mgKOH/g, (ASTM 2896)	7.57

*Test results are based on sample.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: www.adrollubricants.com Email: info@adrollubricants.com Customer Care No.: 8285005500

