



## **ADROL ELITE 4T**

API SN, SAE 20W-40

### **FOUR-STROKE MOTORCYCLE ENGINE OIL**

---

#### **DESCRIPTION**

ADROL ELITE4T 20W40 API SN grade engine Oil is a high performance 4 Stroke Motor Cycle engine oil. It is superior multi grade detergent type lubricating oil meeting the highest API performance level for petrol engine of Motorcycle.

#### **APPLICATIONS**

- Air and liquid-cooled four-stroke motorcycle engines
- Particularly suitable for Japanese high performance motorcycle engines
- Motorcycles with and without oil immersed clutches
- Motorcycles with combined engine/transmission units or separate gear boxes where a multigrade engine oil is specified
- Motorcycles with back torque limiters
- Motorcycles with exhaust catalytic converters
- Latest generation, four-stroke scooter engines
- Four-stroke gasoline engines fitted to portable power equipment, such as generators, mowers, etc

#### **PERFORMANCE STANDARDS**

- API SN
- JASO MA2

#### **BENEFITS**

- Prolongs engine life
- Saves on maintenance
- Lively throttle response
- Good all-temperature protection

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."





**GARGO INTERNATIONAL**  
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases  
Steel Grip Conveyor Belts, Transmission Rubber Belts

### KEY PROPERTIES

SAE GRADES	20W-40
Appearance	Clear & bright
Relative Density @ 29.5°C,g/ml	0.872
Viscosity @ 40°C (mm <sup>2</sup> /s)	128.62 cSt
Viscosity @ 100°C (mm <sup>2</sup> /s)	15 cSt
Viscosity Index	136
Pour Point (°C)	-18
Flash Point (°C)	225
TBN, mgKOH/g, (ASTM 2896)	7.57

\*Test Results are based on the Samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: [www.adrollubricants.com](http://www.adrollubricants.com) Email: [info@adrollubricants.com](mailto:info@adrollubricants.com) Customer Care No.: 8285005500

