



## **ADROL MAGIC ACE**

**API CF, SAE 15W40**

### **DIESEL ENGINE OIL**

#### **DESCRIPTION**

**ADROL MAGIC ACE 15W-40 CF** is a Premium performance, multi-grade, diesel engine oil specifically designed to lubricate a wide range of diesel engines that require performance lubricants operating under the most severe service conditions.

#### **APPLICATIONS**

- Mixed fleets of diesel engines (high-speed, turbocharged or naturally aspirated)
- Three / Four Wheel light duty commercial vehicles
- Mixed fleets including both old and new equipment

#### **PERFORMANCE STANDARDS**

- API SG-CD

#### **BENEFITS**

- Excellent deposit control on valves and piston crown lands reduces oil consumption.
- Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue.
- Outstanding valve train wear protection maintains fuel economy.
- Exceptional soot dispersions keeps fuel soot in suspension, avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.

#### **TYPICAL PROPERTIES**

SAE GRADES	15W-40
Viscosity @ 100°C (mm <sup>2</sup> /s)	115
Viscosity @ 40°C (mm <sup>2</sup> /s)	15
Viscosity Index	130
Pour Point (°C)	-15
Flash Point (°C)	210
Base Number D2896, MgKOH/g	5.1

\*Test results based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

