



## **ADROL GEO**

**API SF/CD, SAE 20W-50**

### **GAS ENGINE OIL (GEO/CNG)**

---

#### **DESCRIPTION**

**Adrol GEO (GAS ENGINE OIL)20W-50** is formulated to meet API SG / CD performance requirement. It is blended using high quality base oils, shear stable viscosity improver, performance proven engine oil additives and pour point depressant. It is multi-grade engine oil for use all round the year.

#### **APPLICATIONS**

- Recommend for use in all LPG /CNG/ Petrol engines of passenger cars, 3-wheeler and small delivery vans.
- Mixed fleets of diesel engines (high-speed, four-stroke, turbocharged or naturally aspirated)
- Three / Four Wheel light duty commercial vehicles
- Mixed fleets including both old and new equipment

#### **PERFORMANCE STANDARDS**

API SF/CD

#### **BENEFITS**

- Compatible with alternative fuel.
- Excellent TBN retention.
- Low ash forming.
- Exceptional soot dispersancy keeps fuel soot in suspension, avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.
- Excellent deposit control on valves and piston crownlands reduces oil consumption. Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue.
- Outstanding valve train wear protection maintains fuel economy.
- High level of anti-wear additive protects against valve train wear and scuffing of highly loaded parts operating under boundary lubrication conditions

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."





**GARGO INTERNATIONAL**  
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases  
Steel Grip Conveyor Belts, Transmission Rubber Belts

### TYPICAL PROPERTIES

SAE GRADES	20W-50
Viscosity @ 40°C (mm <sup>2</sup> /s)	160.1
Viscosity @ 100°C (mm <sup>2</sup> /s)	18.65
Viscosity Index	131
Pour Point (°C)	-15
Flash Point (°C)	220
TBN, mgKOH/g, (ASTM 2896)	5.1
CCS Viscosity @-15°C,oP	9200

\*Test results based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: [www.adrollubricants.com](http://www.adrollubricants.com) Email: [info@adrollubricants.com](mailto:info@adrollubricants.com) Customer Care No.: 8285005500

