



ADROL SYNTHETIC 5W/40

API SN/CF, SAE 5W-40

PASSENGER MOTOR CAR OIL (PCMO)

DESCRIPTION

Premium performance, multi-grade motor oil formulated from selected synthetic base fluids and race proven additive technology for use in passenger cars and light truck gasoline engines and passenger car diesel engines under all operating conditions. It is optimized to provide complete engine protection plus ultimate performance.

APPLICATIONS

- Naturally aspirated and turbocharged gasoline engines in passenger cars.
- Naturally aspirated and turbocharged diesel engines in passenger cars.
- Gas-fuelled natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended.
- Four-stroke gasoline engines in motorcycles and portable power equipment where the manufacturer recommends conventional passenger car motor oils.

PERFORMANCE STANDARDS

- API SN/CF • ACEA A3/B3-08, A3/B4-08, ACEA C3-08

BENEFITS

- Maximum engine life, power & performance.
- Minimum maintenance costs.
- Low oil consumption.

KEY PROPERTIES

SAE Grade 10W-30	5W-40
Kinematic Viscosity @ 100 °C (mm ² /s)	13
Kinematic Viscosity @ 40 °C (mm ² /S)	92
Viscosity Index	172
Pour Point (°C)	-21
Flash Point (°C)	220
TBN (mgKOH/g)	6.6

*Test results based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

