

GARGO INTERNATIONAL An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL SUPER KINGS

API SN-CH, SAE 10W-40

PASSENGER CAR MOTOR OIL (PMCO)

DESCRIPTION

ADROL SUPER KINGS 10W/40 API SN-CH Engine Oils is premium, high performance multi-grade engine oil formulated from high quality base oils and combined with modern performance additives to help provide long engine life and protect critical engine parts from lubricant related failures, providing wide temperature range protection.

APPLICATIONS

Can be used in Petrol, Diesel & LPG engines.

PERFORMANCE STANDARDS

API SN-CH

BENEFITS

- Superior engine wear protection.
- Superior cleansing technology to help stop dirt and sludge build up.
- Reduced high temperature engine deposits.
- Superior engine protection during start up, warm-up and normal driving conditions.
- Long-term wear protection of engine parts (distribution, ring, plunger and liner) increasing engine life.
- Excellent thermal and oxidation stability.
- Reduces wear due to advanced base oils.
- Helps clean and protect older engines.
- Meets the most demanding car manufacturer's requirements.
- Ensures the important engine seals stay soft and pliable to minimize oil leakage.

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."





GARGO INTERNATIONAL

An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases Steel Grip Conveyor Belts, Transmission Rubber Belts

KEY PROPERTIES

SAE GRADES	10W-40
Viscosity @ 100°C (mm²/s)	13
Viscosity @ 40°C (mm²/s)	92
Viscosity Index	151
Pour Point (°C)	-24
Flash Point (°C)	220
TBN, mgKOH/g, (ASTM 2896)	6.8

^{*}Test results based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

