



GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL ARB TURBO

API CI4+, SAE 15W-40

DIESEL ENGINE OIL (DEO)

DESCRIPTION

ADROL ARB TURBO 15W40 CI4+ is premium performance semi synthetic multi- grade, heavy-duty diesel engine oil. It is specifically designed to meet the requirements of a wide range of modern, high performance diesel engines where API CI-4+ performance is required. It is formulated with high quality base oils and advanced technology additives which protect the engine to provide excellent performance.

APPLICATIONS

- Modern engines fitted with emission control devices like EGR.
- Engines designed to meet BS6 emission standards.
- Construction and mining vehicles and plant equipment.
- Tractors and farm machinery.
- Generator sets.
- Stop-and-go vehicles in high soot loading service such as buses and trucks.

PERFORMANCE STANDARDS

API CI4+

BENEFITS

- Excellent soot control technology to prevent soot accumulation.
- High performance base oils coupled with special additives ensure high performance even after prolonged use.
- Excellent anti wear detergency properties help to keep the engine clean.
- Minimizes fleet maintenance, operating and inventory costs.

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: www.adrollubricants.com Email: info@adrollubricants.com Customer Care No.: 8285005500





TYPICAL PROPERTIES

SAE GRADES	15W-40
Viscosity @ 40°C (mm ² /s)	114
Viscosity @ 100°C (mm ² /s)	14.9
Viscosity Index	135
Pour Point (°C)	-21
Flash Point (°C)	225
TBN, mgKOH/g, (ASTM 2896)	10.5

*Test results based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

