



GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL ARB PLUS

API CH4, SAE 20W-40

DIESEL ENGINE OIL

DESCRIPTION

ADROL ARB PLUS 20W40 API CH4 is superior quality engine Oil blended with superior quality high Viscosity Index base oils and contains well balanced group of additives, to provide high detergency, dispersancy and anti-oxidation characteristics.

APPLICATIONS

- Mixed fleets of diesel engines (high-speed, four-stroke, turbocharged or naturally aspirated).
- Construction equipment including both old and new equipment.
- Commercial road transport machineries including the latest electronic controlled engines.
- Off-highway vehicles and plant.

PERFORMANCE STANDARDS

API CH4

BENEFITS

- Better resistance against wear of moving engine parts at all operating conditions.
- Protects engine components against rust and corrosion due to built-in alkaline reserves.
- Excellent thermal and oxidation stability & less formation of oxidation related deposits.
- Ensures smooth running of engine in all climatic conditions.
- Exceptional soot handling capability avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.
- Excellent deposit control on valves and piston crown lands reduces oil consumption.
- Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue.

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: www.adrollubricants.com Email: info@adrollubricants.com Customer Care No.: 8285005500





TYPICAL PROPERTIES

SAE GRADES	20W-40
Appearance	Red
Viscosity @ 100°C (mm ² /s)	15.5
Viscosity @ 40°C (mm ² /s)	125-130
Viscosity Index	130
Pour Point (°C)	-18
Flash Point (°C)	220
TBN, mgKOH/g, (ASTM 2896)	10.5

*Test results based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

