



GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL ELITE SUPREME

API CH4, SAE 15W-40

HIGH PERFORMANCE DIESEL ENGINE OIL

DESCRIPTION

ADROL ELITE SUPREME 15W40 API CH4+ is diesel engine oil is a high performance diesel engine oils that help increase engine life in the most severe on and off highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation and After-treatment Systems with Diesel Particulate Filters and Diesel Oxidation Catalysts. Fully backwards compatible, SAE 15W40 diesel engine oil will also deliver the same outstanding performance in older conventional engines.

APPLICATIONS

Recommended for all kinds of Diesel Cars, SUVs, MPVs, trucks, tractors and agricultural equipment.

PERFORMANCE STANDARDS

API CH4

BENEFITS

- High performance engine oil specially formulated from selective base oils and additive packages to meet the lubrication requirements of all the new generation.
- Diesel Passenger Vehicles.
- The Multi-grade property ensures that the oil can be used for all climatic conditions.
- Designed for lubrication vehicles with Naturally Aspirated or Turbocharged diesel engines both in city, on and off highway roads.
- The excellent anti-wear property ensures reduction in engine wear, thus prolonging the life of the engine.
- The oil has very good detergent & dispersant property which keeps the engine parts clean.
- Excellent control on oil thickening.

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: www.adrollubricants.com Email: info@adrollubricants.com Customer Care No.: 8285005500





TYPICAL PROPERTIES

SAE GRADES	15W-40
Appearance	Red
Viscosity @ 100°C (mm ² /s)	115
Viscosity @ 40°C (mm ² /s)	112
Viscosity Index	137
Pour Point (°C)	-21
Flash Point (°C)	220
TBN, mgKOH/g, (ASTM 2896)	7.8

* Test results are based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

