



ADROL GLIDEFULLY SYNTHETIC ENGINE OIL

API CK4, SAE 0W-40

HIGH PERFORMANCE DIESEL ENGINE OIL

DESCRIPTION

ADROL GLIDE0W-40 Fully Synthetic Engine Oil is the leading and newest technology synthetic motor engine oil delivering ultimate performance and protection.

Adrol Glide 0W-40 Full Synthetic Motor Oil is engineered for the latest gasoline and diesel engine technology delivering excellent all-round performance. It provides exceptional cleaning power, wear protection and overall performance. AdrolGlide 0W-40 keeps your engine running like new in all driving conditions.

APPLICATIONS

Adrol0W-40 is recommended for many types of modern vehicles where it will help provide unsurpassed performance even under very demanding driving conditions.

- It is recommended for all trucks, buses, Tractors, JCBs, dumpers and other heavy loading vehicles and meets the requirement of BS6 engines.
- Latest engine technologies including Turbo-chargers, Direct Injection, Diesels (without DPF) and Hybrids
- High performance engines
- Most operating conditions, from mild to extreme

PERFORMANCE STANDARDS

- API CK4
- API CI4+
- API CI4
- API CH4

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."





BENEFITS

Adrol Glide 0W-40 is made with a proprietary blend of ultra-high performance synthetic base stocks fortified with a precisely balanced component system.

- Saves fuel of vehicles up to 20%.
- Better driving experience of car due to lesser engine vibration even at higher speed.
- Better pick-up of car
- Lesser smoke emissions from vehicle
- Extended drain period up to 1.5 to 2 times.

TYPICAL PROPERTIES

SAE GRADES	0W-40
Appearance	Clear & bright
Relative Density @ 29.5°C,g/ml	0.825
Viscosity @ 40°C (mm ² /s)	72cSt
Viscosity @ 100°C (mm ² /s)	13.2cSt
Viscosity Index	180
Pour Point (°C)	-33
Flash Point (°C)	245
TBN, mgKOH/g, (ASTM 2896)	9.2

*Test Results are based on the Samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

