

## GARGO INTERNATIONAL An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases Steel Grip Conveyor Belts, Transmission Rubber Belts

# **ADROL BRAKE OIL DOT 4**

### BRAKEFLUID

#### DESCRIPTION

ADROL BRAKE FLUID DOT 4is a high performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems. ADROL Brake Fluid DOT 4 is based on polyethylene glycol ether technology to provide a high level of brake and clutch performance in automotive and commercial vehicles.

#### **APPLICATIONS**

Recommended for all types of automotive and commercial vehicles.

#### **PERFORMANCE STANDARDS**

DOT 4

#### **BENEFITS**

- Consistent and safe brake performance under high braking.
- Reduces leakage and loss of fluid to a minimum.
- Improved life and reliability of brake system components.
- High boiling point.
- Minimum rubber component swell.
- Excellent corrosion protection.

#### **TYPICAL PROPERTIES**

Appearance	Clear and bright yellow liquid
Density @ 20 °C (g/ml)	1.07
Equillibrium Reflux Boiling Point (ERBP) ASTM	260
D1120	
Viscosity I, Kinematic @ 40 °C (mm <sup>2</sup> /S)	1200
Wet Reflux Boiling Point	165
рН	8.0
Water Content	0.15%

\*Test results are based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."



536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: www.adrollubricants.com Email: info@adrollubricants.com Customer Care No.: 8285005500