



## ADROL TQ

### AUTO TRANSMISSION STEERING OIL (TQ)

---

#### DESCRIPTION

**ADROL TQ AUTO TRANSMISSION STEERING OIL** is a high quality automatic transmission fluid manufactured from highly refined base stocks and carefully selected additives, to provide a superior performance in the automatic transmission systems of automotive. ADROL TQ AUTO TRANSMISSION STEERING OIL A provides superior protection for the automatic transmission system against wear & corrosion, while its high viscosity index ensures unmatched lubrication at high operating temperatures.

#### APPLICATIONS

Trans Fluid is recommended for use in power steering units of passenger cars and commercial vehicles, Light Trucks, automatic transmissions and certain manual transmissions of vehicles.

#### BENEFITS

- Superior oxidation and thermal stability reduce deposit formation.
- Superior anti-wear protection to critical parts
- Very high viscosity index and low pour point ensures proper lubrication in both high temperature operation & low starting temperatures.
- Good shear stability implies a longer service life of oil and the hardware.
- Good foam control leads to smooth gear shifting.
- Compatible with all common elastomers.
- Provides good protection against rust and corrosion

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."





## TYPICAL PROPERTIES

Characteristics	Method	Value
Colour	Visual	Red
Appearance	Visual	Clear and Bright
Density @15°C, g/cc	ASTM D1298	0.8782
Kinematic Viscosity @40°C, cSt	ASTM D445	39.8
Kinematic Viscosity @100°C, cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	158
Copper Corrosion, 100°C, 3 hrs.	ASTM D130	1a
Flash Point, °C	ASTM D92	205
Pour Point, °C	ASTM D97	-42

\*Test results are based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

