



## ADROL AIR COMPRESSOR OIL 68

### AIR COMPRESSOR OIL

#### DESCRIPTION

**ADROL COMPRESSOR OIL** is premium quality specially developed for oil flooded screw and sliding vane type compressor to provide satisfactory lubrication under wide range of operating temperatures and load conditions. ADROL compressor oil 68 reduces sludge deposits.

#### APPLICATIONS

Recommended for use in oil flooded screw compressors and sliding vane.

#### PERFORMANCE STANDARDS

- SO 6743 - DAH
- DIN 51506 VDL

#### BENEFITS

- Excellent oxidation and thermal stability.
- Improved water separability.
- Low wear to improve anti-wear and lubricating properties.
- Excellent performance at high temperature and good start ability in cold temperature.

#### KEY PROPERTIES

Grade	68
Kinematic Viscosity @40°C (mm <sup>2</sup> /s)	67.76
Kinematic Viscosity @100°C (mm <sup>2</sup> /s)	9.10
Viscosity Index	110
TAN	0.57
Flash Point (°C, COC)	200
Demulsibility @ 54°C 40-40-0 (10)	40-40-0 (10))
Rust Test D665 (A&B), 24hrs	PASS

\*Test results are based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

