

GARGO INTERNATIONAL

An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL HEAT THERMIC TRANSFER OIL

HEAT THERMIC TRANSFER OIL

DESCRIPTION

ADROL HEAT TRANSFER OIL s premium quality heat transfer oil intended for use in closed indirect heating systems. It is formulated from highly refined base stocks to provide excellent oxidation stability and resistance against thermal cracking. It possesses high specific heat and thermal conductivity that provide faster heat transfer. Its ability to flow rapidly at low temperatures ensures quick circulation at start-up and reduced risk of local over-heating.

APPLICATIONS

- Open systems operating at temperatures upto 180°C.
- Closed, indirect heating systems equipped with expansion tanks in all kinds of industrial processes operating at bulk oil temperatures up to 285°C.

BENEFITS

- Excellent thermal and oxidation stability minimizes deposit formation and viscosity increase leading to extended service life and reduced downtime.
- High specific heat and thermal conductivity of this oil provides more rapid heat dissipation.
- Exceptional resistance to thermal cracking and decomposition enables this oil to perform well.
- Non-corrosive and Non-toxic.
- Superior low temperature fluidity ensures quick circulation at start-up and reduced risk of local overheating.

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

SUPERHERO



GARGO INTERNATIONAL

An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases Steel Grip Conveyor Belts, Transmission Rubber Belts

KEY PROPERTIES

Grade	32
Density, kg/liter @29.5°C	0.874
Kinematic Viscosity @40°C (mm2/s)	30.2
Kinematic Viscosity @100°C (mm2/s)	5
Viscosity Index	90
Flash Point (°C, COC)	210
Copper Corrosion, 3hr@100°C	1a

Temperature	100	150	200	250	300	340
Specific Heat, kJ/Kg Deg. K	2.05	2.3	2.5	2.7	2.8	3
Thermal Conductivity,	0.12	0.12	0.125	0.115	0.112	0.1
W/m2 Deg K						

^{*}Test results are based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

