



ADROL ELITE PREMIUM GEAR OIL

80W-90/85W-140

EXTREME PRESSURE GEAR OIL

DESCRIPTION

ADROL ELITEPREMIUM GEAR OIL is extreme pressure automotive gear oil lubricant. It is blended from selected base stocks and contain additives to provide extreme pressure, anti-rust ,anti-corrosion characteristics.

APPLICATIONS

- Recommended for all types of industrial and mobile equipment requiring mild EP gear lubricants
- Particularly recommended for enclosed gear drives and speed reducers, ranging from small gearboxes to large, high-power units on metal rolling mills, cement mills, sugar mills and mine hoist
- Also suitable for chain cases, sprockets, slide guides, flexible coupling, plain and rolling element bearings.

PERFORMANCE STANDARDS

- ANSI/AGMA 9005-D94[EP]
- U.S. Steel 224
- David Brown Table E approved
- DIN 51517 Part 3 CLP

BENEFITS

- Extends gear life due to high load carrying capacity and outstanding ability to keep gear surface free of deposits
- Provides long oil service life through excellent oxidation resistance
- Allow rapid separation of water
- Protects against rust and corrosion
- Compatible with all elastomers & other sealing materials.

DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."





GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

TYPICAL PROPERTIES

SAE GRADES	80W-90	85W-140
Viscosity @ 100°C (mm ² /s)	19	30
Viscosity @ 40°C (mm ² /s)	220	460
Viscosity Index	95	95
Pour Point (°C)	-18	-15
Flash Point (°C, COC)	215	240

*Test results are based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

536, Punjabi Basti, 3rd Floor, Main Rohtak Road, Near Metro Pillar No. 374, Nangloi, Delhi - 110041

Web.: www.adrollubricants.com Email: info@adrollubricants.com Customer Care No.: 8285005500

