

GARGO INTERNATIONAL

An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL 4T SCOOTY API SN/ JASO MB/ SAE 10W-30

SCOOTER ENGINE OIL

DESCRIPTION

Adrol 4T Scooty is formulated with high performance additive system meeting the requirement of current advanced top —tier engine oil grade API SN. It is optimize to provide complete scooter oil performance especially for Fuel economy and Durability

APPLICATIONS

• Four stroke petrol engines of Automatic scooters

PERFORMANCE STANDARDS

• API SN; JASO MB

BENEFITS

- Extended Drain Interval
- Better Fuel Economy
- Excellent wear protection

KEY PROPERTIES

SAE Grade 10W-30	10W-30
Kinematic Viscosity @ 100 °C (mm ² /s)	9
Kinematic Viscosity @ 40 °C (mm ² /S)	61.5
Viscosity Index	138
Pour Point (°C)	-29
Flash Point (°C)	230
TBN (mgKOH/g)	7.4

^{*}Test results are based on samples.



DISCLAIMER: "This message is intended only for the use of the addressee and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this e-mail in error, please notify us immediately by return e-mail and delete this e-mail and all attachments from your system."

