



ADROL SPRINT 4T

API SL, SAE 20W-40

FOUR-STROKE MOTORCYCLE ENGINE OIL

DESCRIPTION

ADROL SPRINT4T 20W40 API SL is high quality engine oil designed to meet the requirements of four-stroke motorcycle engines.

APPLICATIONS

- Air and liquid-cooled four-stroke motorcycle engines
- Particularly suitable for Japanese high performance motorcycle engines
- Motorcycles with and without oil immersed clutches
- Motorcycles with combined engine/transmission units or separate gear boxes where a multigrade engine oil is specified
- Motorcycles with back torque limiters
- Motorcycles with exhaust catalytic converters
- Latest generation, four-stroke scooter engines
- Four-stroke gasoline engines fitted to portable power equipment, such as generators, mowers, etc.

PERFORMANCE STANDARDS

- API SL
- JASO MA2

BENEFITS

- Prolongs engine life
- Saves on maintenance
- Lively throttle response
- Good all-temperature protection



GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

KEY PROPERTIES

SAE GRADES	20W-40
Appearance	Red& Bright
Viscosity @ 40°C (mm ² /s)	128cSt
Viscosity @ 100°C (mm ² /s)	15 cSt
Viscosity Index	126
Pour Point (°C)	-18
Flash Point (°C)	220
TBN, mgKOH/g, (ASTM 2896)	5.3

*Test Results are based on the Samples.

