

GARGO INTERNATIONAL

An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL ROYALE API SN, JASO MA2, SAE 15W-50

MOTORCYCLE ENGINE OIL

DESCRIPTION

ADROL ROYALEOil for Racing and Off-road / Enduro bikes fitted with high performance 4 stroke engines, integrated gearbox or not, wet or dry clutch, racing engines running at very high temperature and at very high speed (RPM): sports bikes, speed bikes, SuperSport, endurance, uphill / drag races, dirt bikes and MX, ATV etc.

APPLICATIONS

- Air and liquid-cooled four-stroke motorcycle engines
- Motorcycles with exhaust catalytic converters
- Suitable for all motorcycle engines, both carburetor and fuel injected where API SN or below and JASO MA and MA 2 are recommended.

PERFORMANCE STANDARDS

• API SN • JASO MA2

BENEFITS

- Allows the engine to develop the same power as when new, even after an extended duration of speed, high load, and high temperature running.
- Exceptional cleanliness performance delivers power protection throughout the complete oil drain interval.
- Superior protection of engine, clutch and gears.
- Complies with requirements of catalyst equipped engines Prolongs engine life.

KEY PROPERTIES

SAE GRADES	15W-50
Viscosity @ 100°C (mm²/s)	17.3cSt
Viscosity @ 40°C (mm²/s)	130.9 cSt
Viscosity Index	145
Pour Point (°C)	-33
Flash Point (°C)	246
TBN, mgKOH/g, (ASTM 2896)	7.8

^{*}Test Results are based on sample.



