



## **ADROL MAX 4T**

API SJ, SAE 20W-40

### **FOUR-STROKE MOTORCYCLE ENGINE OIL**

---

#### **DESCRIPTION**

ADROL MAXT 4T 20W40 API SJ is high quality engine oil designed to meet the requirements of four-stroke motorcycle engines.

#### **APPLICATIONS**

- Air and liquid-cooled four-stroke motorcycle engines
- Particularly suitable for Japanese high-performance motorcycle engines
- Motorcycles with and without oil immersed clutches
- Motorcycles with combined engine/transmission units or separate gear boxes where a multigrade engine oil is specified
- Motorcycles with back torque limiters
- Motorcycles with exhaust catalytic converters
- Latest generation, four-stroke scooter engines
- Four-stroke gasoline engines fitted to portable power equipment, such as generators, mowers, etc.

#### **PERFORMANCE STANDARDS**

- API SJ
- JASO MA2

#### **BENEFITS**

- Prolongs engine life
- Saves on maintenance
- Lively throttle response
- Good all-temperature protection





**GARGO INTERNATIONAL**  
An ISO 9001:2015 Certified Co.

Manufactures of Adrol Lubricants and Creases  
Steel Grip Conveyor Belts, Transmission Rubber Belts

## TYPICAL PROPERTIES

SAE GRADES	20W-40
Appearance	Red & Bright
Viscosity @ 40°C (mm <sup>2</sup> /s)	117.7 cSt
Viscosity @ 100°C (mm <sup>2</sup> /s)	14.10 cSt
Viscosity Index	120
Pour Point (°C)	-18
Flash Point (°C)	236
TBN, mgKOH/g, (ASTM 2896)	5.3

Test results based on sample.

