

GARGO INTERNATIONAL

An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL SUPER SYNTHETIC 5W-30

API SN/CH, SAE 5W-30

PASSENGER MOTOR CAR OIL (PCMO)

DESCRIPTION

Adrol Super Synthetic 5W-30 is a premium performance, multi-grade motor oil formulated from selected synthetic base fluids and race proven additive technology for use in passenger cars and light truck gasoline engines and passenger car diesel engines under all operating conditions. It is optimized to provide complete engine protection plus ultimate performance.

APPLICATIONS

- Naturally aspirated and turbocharged gasoline engines in passenger cars.
- Naturally aspirated and turbocharged diesel engines in passenger cars.
- Gas-fueled natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended.
- Four-stroke gasoline engines in motorcycles and portable power equipment where the manufacturer recommends conventional passenger car motor oils.

PERFORMANCE STANDARDS

- API SN/CF
- ACEA A3/B3-08, A3/B4-08, ACEA C3-08

BENEFITS

- Maximum engine life, power & performance.
- Minimum maintenance costs.
- Low oil consumption.

TYPICAL PROPERTIES

SAE Grade	5W-30
Kinematic Viscosity @ 100 °C (mm²/s)	13
Kinematic Viscosity @ 40 °C (mm²/S)	92
Viscosity Index	151
Pour Point (°C)	-21
Flash Point (°C)	228
TBN (mgKOH/g)	7.5

^{*}Test results based on samples.



