



ADROL MAX ENGINE OIL

API CF-4, SAE 15W40

DIESEL ENGINE OIL

DESCRIPTION

ADROL MAX 15W-40 CF-4 is a premium performance, multi-grade, diesel engine oil specifically designed to lubricate a wide range of diesel engines that require performance lubricants operating under the most severe service conditions.

APPLICATIONS

- Mixed fleets of diesel engines (high-speed, turbocharged or naturally aspirated)
- Three / Four Wheel light duty commercial vehicles
- Mixed fleets including both old and new equipment

PERFORMANCE STANDARDS

- API SF

BENEFITS

- Excellent deposit control on valves and piston crown lands reduces oil consumption.
- Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue.
- Outstanding valve train wear protection maintains fuel economy.
- Exceptional soot dispersions keeps fuel soot in suspension, avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.

TYPICAL PROPERTIES

SAE GRADES	15W-40
Viscosity @ 100°C (mm ² /s)	115
Viscosity @ 40°C (mm ² /s)	15
Viscosity Index	130
Pour Point (°C)	-15
Flash Point (°C)	210
Base Number D2896, MgKOH/g	5.1

*Test results based on samples.

