



## **ADROL ARB PLUS**

**API CH4, SAE 20W-40**

### **DIESEL ENGINE OIL**

---

#### **DESCRIPTION**

**ADROL ARB PLUS 20W40 API CH4** is superior quality engine Oil blended with superior quality high Viscosity Index base oils and contains well balanced group of additives, to provide high detergency, dispersancy and anti-oxidation characteristics.

#### **APPLICATIONS**

- Mixed fleets of diesel engines (high-speed, four-stroke, turbocharged or naturally aspirated).
- Construction equipment including both old and new equipment.
- Commercial road transport machineries including the latest electronic controlled engines.
- Off-highway vehicles and plant.

#### **PERFORMANCE STANDARDS**

API CH4

#### **BENEFITS**

- Better resistance against wear of moving engine parts at all operating conditions.
- Protects engine components against rust and corrosion due to built-in alkaline reserves.
- Excellent thermal and oxidation stability & less formation of oxidation related deposits.
- Ensures smooth running of engine in all climatic conditions.
- Exceptional soot handling capability avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.
- Excellent deposit control on valves and piston crown lands reduces oil consumption.
- Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue.



### TYPICAL PROPERTIES

SAE GRADES	20W-40
Appearance	Red
Viscosity @ 100°C (mm <sup>2</sup> /s)	15.5
Viscosity @ 40°C (mm <sup>2</sup> /s)	125-130
Viscosity Index	130
Pour Point (°C)	-18
Flash Point (°C)	220
TBN, mgKOH/g, (ASTM 2896)	10.5

\*Test results based on samples.

