



ADROL ELITE PREMIUM GEAR OIL

80W-90/85W-140

EXTREME PRESSURE GEAR OIL

DESCRIPTION

ADROL ELITEPREMIUM GEAR OIL is extreme pressure automotive gear oil lubricant. It is blended from selected base stocks and contain additives to provide extreme pressure, anti-rust ,anti-corrosion characteristics.

APPLICATIONS

- Recommended for all types of industrial and mobile equipment requiring mild EP gear lubricants
- Particularly recommended for enclosed gear drives and speed reducers, ranging from small gearboxes to large, high-power units on metal rolling mills, cement mills, sugar mills and mine hoist
- Also suitable for chain cases, sprockets, slide guides, flexible coupling, plain and rolling element bearings.

PERFORMANCE STANDARDS

- ANSI/AGMA 9005-D94[EP]
- U.S. Steel 224
- David Brown Table E approved
- DIN 51517 Part 3 CLP

BENEFITS

- Extends gear life due to high load carrying capacity and outstanding ability to keep gear surface free of deposits
- Provides long oil service life through excellent oxidation resistance
- Allow rapid separation of water
- Protects against rust and corrosion
- Compatible with all elastomers & other sealing materials.



GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

TYPICAL PROPERTIES

SAE GRADES	80W-90	85W-140
Viscosity @ 100°C (mm ² /s)	19	30
Viscosity @ 40°C (mm ² /s)	220	460
Viscosity Index	95	95
Pour Point (°C)	-18	-15
Flash Point (°C, COC)	215	240

*Test results are based on samples.

