



GARGO INTERNATIONAL
An ISO 9001:2008 Certified Co.

Manufactures of Adrol Lubricants and Creases
Steel Grip Conveyor Belts, Transmission Rubber Belts

ADROL ARB TURBO

API CI4+, SAE 15W-40

DIESEL ENGINE OIL (DEO)

DESCRIPTION

ADROL ARB TURBO 15W40 CI4+ is premium performance semi synthetic multi- grade, heavy-duty diesel engine oil. It is specifically designed to meet the requirements of a wide range of modern, high performance diesel engines where API CI-4+ performance is required. It is formulated with high quality base oils and advanced technology additives which protect the engine to provide excellent performance.

APPLICATIONS

- Modern engines fitted with emission control devices like EGR.
- Engines designed to meet BS6 emission standards.
- Construction and mining vehicles and plant equipment.
- Tractors and farm machinery.
- Generator sets.
- Stop-and-go vehicles in high soot loading service such as buses and trucks.

PERFORMANCE STANDARDS

API CI4+

BENEFITS

- Excellent soot control technology to prevent soot accumulation.
- High performance base oils coupled with special additives ensure high performance even after prolonged use.
- Excellent anti wear detergency properties help to keep the engine clean.
- Minimizes fleet maintenance, operating and inventory costs.





TYPICAL PROPERTIES

SAE GRADES	15W-40
Viscosity @ 40°C (mm ² /s)	114
Viscosity @ 100°C (mm ² /s)	14.9
Viscosity Index	135
Pour Point (°C)	-21
Flash Point (°C)	225
TBN, mgKOH/g, (ASTM 2896)	10.5

*Test results based on samples.

